

Is Your Product Registered? Contact your Dealer to verify. Warranties are based on Registrations and reduced to 1 year without Registration.



| 101N | 842521 AN-8 NITRILE GASKET | S |
|-------------|--|---------------------|
| 105 | 842522 VALVE SPRING | |
| 120 | 842523 ELBOW | Pla (7 5 |
| 121 | 842524 MIXER VALVE | adj |
| 122 | 842525 1mm. DIAMETER NOZZLE | ass |
| 127 | 842526 CONIC NUT | tan |
| 131 | 842527 16x2 FLAT GASKET | gri (15 |
| 136N | 842528 AN-5 NITRILE GASKET | wil |
| 138 | 842529 10mm DIAMETER CONE | (75 |
| 141 | 842530 BLACK TUBE LANCE | acl |
| 151 | 842531 40mm X 1.50 m. STRAP | ade |
| 156 | 842532 HANDLE | |
| 157 | 842533 COVER SCREW | М |
| 158 | 842534 CHAMBER COVER | |
| 159N | 842535 AN-30 NITRILE GASKET | Cle |
| 160 | 842536 CHAMBER | of€ |
| 164 | 842537 NECK SEAL | am NE |
| 165 | 842538 VITON CHAMBER VALVE | |
| 168V | 842539 2-104 VITON GASKET | Ave |
| 191 | 842540 NOZZLE NUT | ind |
| 195 | 842541 HOSE NUT | of v |
| 196 | 842542 HOSE BUSHING | |
| 530 | 842543 HANDLE BODY | S/ |
| 531 | 842544 BUTTON | Sto |
| 532 | 842545 BUTTON BOLT | rea |
| 533 | 842546 HANDLE CLIP | pre |
| 534 | 842547 HANDLE NUT | Pro COI |
| 535 | 842548 HANDLE FILTER | for |
| 536 | 842549 HANDLE SPRING | pro |
| 537 | 842550 SHUTTER | <u>Tre</u> |
| 538 | 842551 2-121 NITRILE GASKET | ea ad |
| 539 | 842552 2-109 VITON GASKET | <u>Cle</u> |
| 540 | 842553 2-107 VITON GASKET | wa |
| 726 | 842554 ELBOW WITH NOZZLE | Ad |
| 728 | 842555 TUBE WITH NUTS | ne: fre: |
| 739 | 842556 COMPLETE CHAMBER | IIC. |
| 743 | 842557 SEALING VALVE | |
| 750 754 | 842558 COMPLETE HANDLE | G |
| 751 757 | 842559 COMPLETE SHUTTER | Str "P |
| 757 795 | 842560 COMPLETE HOSE | "p ext |
| 785 705 | 842562 7 LITER TANK 842564 COMPLETE LANCE | flar |
| 795 1415 | | US |
| 1415 | 842642 REPAIR KIT (842521, 842528, | spi |
| | 842535, 842537, 842538, 842552, 842553) | ma ho: |
| | 842553) | 110. |

START-UP

Place strap on both sides of the bottle and follow the drawing. Fit the hose (757) to the bottom of the tank and to the lance handle (750) firmly adjusting the nuts (195). Place one end of the tube (728) on the handle assembly (750) and the other end on the elbow assembly (726). Once the tank is filled, screw in the chamber assembly (739) to the tank using the grip (156). Pressurize by pumping 25 to 30 times with the pump handle (156). In case that the maximum pressure is exceeded, the sealing valve will activate (743) releasing excess pressure. To work, pump the handle (750) and adjust the nozzle (122) rotating to one side or another to achieve the desired atomization. During usage, pressure will diminish and additional pumping will be required.




MAINTENANCE – MORE FREQUENT DAMAGES

Clean the equipment and its liquid circuits, including the filter at the completion of each working day. Cleaning should be done with clean water or as small amount of household detergent to the tank.

NEVER LEAVE THE EQUIPMENT PRESSURIZED OR WITH CHEMICAL IN THE TANK.

Avoid gaskets drying out or add some drops of oil (non edible) in the parts indicated in the drawing. If the nozzle is obstructed, (122) clean it with a stream of water or non metallic instruments taking care that the outlet hole is not



SAFETY STANDARDS AND HANDLING OF CHEMICAL SPRAY PRODUCTS Storage. Place the product in an exclusive, ventilated and locked storeroom with key box, out of the reach of children and pets. Store the product in its original packing. Use the same room to store mixing, preparation and application utensils.


Product Preparation. Verify that that the product and treatment equipment are not expired and are in good condition. Read and follow the instructions provided in the products labels and manuals. Use proper utensils for mixing and preparing and mark them correctly. After preparation, wash your hands and face. Dispose properly of empty packages and leftover products.

<u>Freatment Procedure.</u> Use suitable protective equipment. Avoid contact with the skin and eyes and, do not eat, drink or smoke. Do not apply under windy conditions or against the wind. Avoid any product drifting into adjacent land and crops. Avoid any drift into neighboring springs, rivers, streams, lakes, etc.

<u>Cleanup After Use.</u> Destroy empty packaging and bottles by burning or burying 1 ft/ 30 cm deep, away from water (streams, wells). Clean all spray equipment thoroughly. Wash yourself and your clothes. <u>Advice in case of poisoning.</u> Go to the doctor with the product label, or take the affected person to the nearest hospital. Avoid use of home medicines and, in all cases wash the affected skin areas with plenty of fresh water.


GENERAL PRECAUTIONS

Strictly follow recommendations and warnings on labels for products marked "dangerous" and "poisonous. Comply with the application time and expiration date of each product. Avoid spraying in extremely hot weather. Take precaution when spraying near electrical installations. Never use alkaline, acids, flammable materials or those which may produce combustion processes. The sprayers are intended to be used only with herbicides, insecticides and fungicides for plants. Do not expose them to the sunshine. These sprayers must be safety tested at least annually by specialized personnel. At the time of manufacturing, the manufacturer is aware of no harmful influences from the material of which the device is made. The sprayer hose must be original equipment from the manufacturer. Do not substitute aftermarket components



GUARANTEE

Our products are guaranteed for one year from date of purchase against defects in material and workmanship. This guarantee is strictly limited to the replacement free of charge of parts recognized as defective by our Service Department. The guarantee shall not apply in case of improper use of our materials, disassembling or modifications of our equipments and for those pieces which may require maintenance due to normal wear and tear. This guarantee shall not apply in case of negligence, imprudence and, irrational use. A copy of the original invoice or bill of sale may be required to establish purchase date.



Maruyama U.S., Inc. 3570 Shelby Lane Denton, Texas 76207 940-383-7400 940-383-7466 (Fax) Website: www.maruyama-us.com

